



Unit:mm

- Size: 273mmx220mmx202mm
- Airflow: 868~965m³/hr
511~568CFM
- Weight: 3000g
- Noise: 61~63dBA
- Impeller: PP UL94V-0 Reinforced Plastic
- Frame: PP UL94V-0 Reinforced Plastic
- Connector:AMP350781-1
- Motor: Capacitor-Run Induction and external rotor Motor
- Safety: UL.CE.CUL
- Operation Temperature: -10°C~+70°C

| Model | Bearing System | Voltage VAC | Freq. Hz | Current A | Power W | Speed RPM | Noise dBA | Air Flow | | Static Pressure (mmH ₂ O) | Weight Gram |
|-------------|----------------|-------------|----------|-----------|---------|-----------|-----------|--------------------|---------|--------------------------------------|-------------|
| | | | | | | | | M ³ /hr | CFM | | |
| RCL2720S1-C | Sleeve | 230 | 50/60 | 0.80/0.90 | 150/180 | 1300/1500 | 61/63 | 868/965 | 511/568 | 16.6/23.5 | 1350 |
| RCL2720S2-C | | 115 | 50/60 | 1.4/1.7 | 150/180 | 1300/1500 | 61/63 | 868/965 | 511/568 | 16.6/23.5 | |
| RCL2720B1-C | Ball | 230 | 50/60 | 0.80/0.90 | 150/180 | 1300/1500 | 61/63 | 868/965 | 511/568 | 16.6/23.5 | |
| RCL2720B2-C | | 115 | 50/60 | 1.4/1.7 | 150/180 | 1300/1500 | 61/63 | 868/965 | 511/568 | 16.6/23.5 | |

