

# 承认书

## APPROVAL SHEET

客户 CUSTOMER:

---

产品类别 PRODUCT SERIET: 薄型碳膜电位器 Ultra Thin Micro  
potentiometer

---

产品型号 MODEL NO. : WH0141-2-B50K (  $\phi$  16 $\times$ 2 )

---

## 1. ELECTRICAL CHARACTERISTICS 电气特性

Item	Item 項目	Specification 规格
1.1	Resistance value and tolerance of resistance 阻值及容许偏差	B50K±20%
1.2	Load power 负载功率	0.03 W
1.3	Rotational noise 旋转杂音	68mV max
1.4	Insulation Resistance 绝缘电阻	>100MΩ At 200V DC
1.5	Withstanding Voltage 耐电压	>1Minute At 250V AC
1.6	Max rated voltage 最大工作电压	50V AC
1.7	Tracking error 双联同步误差	
1.8	Residual resistance 残留阻抗	R1,2<10Ω ; R2,3<10Ω
1.9	Switch contact resistance 开关接触阻抗	
1.10	Switch power 开关电力	

## 2. MECHANICAL CHARACTERISTICS 机械特性

2.1	Dimensions 外形尺寸	Refer to the separate product drawing
2.2	Total rotation angle 全回转角度	270±5°
2.3	Rotational Torque 旋转力矩	5~100gf.cm
2.4	Switch working angle 开关动作角度	
2.5	Switch torque 开关力矩	
2.6	Shaft Push& Pull Strength 轴推拉强度	
2.7	Click slip-out force 定位点起动力	
2.8	Shaft Wobble (mm p-p)轴摆动	≤0.3mm
2.9	Shaft Stop Strength 止挡强度	>0.7kg.cm

## 3. DURABILITY CHARACTERISTICS 耐久特性

3.1	Rotating life 旋转寿命	10,000 cycles
3.2	Storage Temperature Range 储藏温度范围	-30℃~+80℃
3.3	Operation Temperature Range 使用温度范围	-20℃~+70℃
3.4	Soldering Heat Characteristic 耐焊锡热	260° C/2.5±0.5S

				LOT.NO 样板编号	
				MODER. 型号	WH0141-2
DWN 拟制	DHK 审核	APPO 批准	DATE 日期	DESCRIPTIO N 描述	Ultra Thin Micro potentiometer 薄型碳膜电位器
陈东		史伟峰	2012-4-5		

