



EI38/13.6 3.2VA

Özellikleri

VDE 0570 / EN 61558 Normuna
Göre Vakum Dolgulu İki Bölmeli
Sarımlı İzolasyon Sınıfı **70° C/B**
Ağırlığı 150 Gr.

Characteristic

According to **VDE 0570 / EN 61558**
Potted under vacuum Split-Bobbin
winding Insulation Class ta **70° C/B**
Weight 150 Gr.



SİPARİŞ KODU Order No.	PRİMER [V] Primary	SEKONDER [V] Secondary	AKIM [mA] Current	PİM ARALIĞI Pim	BOŞTAKI VOLTAJI [V] No-Load Voltage
ASL 130106	230V~	6	533	1 - 5 / 7 - 9	7,7
ASL 130108	230V~	7,5	427	1 - 5 / 7 - 9	9,7
ASL 130109	230V~	9	355	1 - 5 / 7 - 9	11,6
ASL 130112	230V~	12	266	1 - 5 / 7 - 9	15,3
ASL 130115	230V~	15	213	1 - 5 / 7 - 9	19,3
ASL 130118	230V~	18	177	1 - 5 / 7 - 9	23,2
ASL 130124	230V~	24	133	1 - 5 / 7 - 9	31,3
ASL 130206	230V~	2 x 6	2 x 266	1-5/6-7,9-10	2 x 7,7
ASL 130208	230V~	2 x 7,5	2 x 213	1-5/6-7,9-10	2 x 9,7
ASL 130209	230V~	2 x 9	2 x 177	1-5/6-7,9-10	2 x 11,5
ASL 130212	230V~	2 x 12	2 x 133	1-5/6-7,9-10	2 x 15,7
ASL 130215	230V~	2 x 15	2 x 106	1-5/6-7,9-10	2 x 19,7
ASL 130218	230V~	2 x 18	2 x 88	1-5/6-7,9-10	2 x 23,5
ASL 130224	230V~	2 x 24	2 x 66	1-5/6-7,9-10	2 x 31,0