



MP35-12	MP35-24
----------------	----------------

- Constant voltage design
- Universal AC input
- IP67
- 2 years warranty
- Under&Over Voltage protections
- Short circuit / Overload
- Full isolated plastic case
- Class II
- 100% full load burn-in test

SPECIFICATION

MODEL		MP35-12	MP35-24
OUTPUT	DC VOLTAGE	12V	24V
	RATED CURRENT	3A	1.5A
	CURRENT RANGE	0-3A	0-1.5A
	RATED POWER	35W	35W
	RIPPLE and NOISE	150mV	
	VOLTAGE TOLERANCE	±3.0%	±3.0%
	LINE REGULATION	±1.0%	±1.0%
	LOAD REGULATION	±0.5%	±0.5%
INPUT	HOLD UP TIME	50ms/230VAC 20ms/115VAC @FULL LOAD	
	VOLTAGE RANGE	90-264VAC	127-370VDC
	FREQUANCY RANGE	47-63Hz	
	EFFICIENCY (Typ.)	<87%	<89%
	AC CURRENT (Typ.)	1.1A/115VAC 0.7A/230VAC	
	INRUSH CURRENT(Typ.)	COLD START 55A(twidth=510µs measured at 50% Ipeak) at 230VAC	
	MAX. No. of PSUs on 16A	4 units (circuit breaker of type B) / 9 units (circuit breaker of type C) at 230VAC	
	CIRCUIT BREAKER	4 units (circuit breaker of type B) / 9 units (circuit breaker of type C) at 230VAC	
PROTECTION	LEAKAGE CURRENT	0.25mA / 240VAC	
	OVERLOAD	110 ~ 130% rated output power	
	OVER VOLTAGE	13.8 ~ 16.2V	27.6 ~ 32.4V
	OVER TEMP.	+80°C	
ENVIRONMENT	SHORT CIRCUITS	PROTECTED	
	WORKING TEMP.	-30 ~ +65°C (Refer to "Derating Curve")	
	WORKING HUMIDITY	20 ~ 90% RH non-condensing	
SAFETY & EMC	STORAGE TEMP., HUMIDITY	-40 ~ +80°C, 10 ~ 95% RH	
	VIBRATION	10 ~ 500Hz, 2G 10min./1cycle, period for 60min. each along X, Y, Z axes	
	WITHSTAND VOLTAGE	I/P-O/P:3KVAC	
OTHERS	ISOLATION RESISTANCE	I/P-O/P:>100M Ohms / 500VDC / 25°C/ 70% RH	
	EMC EMISSION	EN55032 Class B,EN61000-3-2 Class A,EN61000-3-3	
	EMC IMMUNITY	EN61000-4-2,3,4,5,6,8,11	
PACKING	DIMENSION	135*36*31 (L*W*H)	
	PACKING	0,190Kg: 50pcs / 9,5KG 325*235*180 mm. (L*W*H) 0,0138 m³	

