



Type Designation 4703
 Designation IEC LR03
 System Zn-MnO₂ (Alkaline)
 Shelf Life (Coding)* 10 years
 Nominal Voltage [V] 1.5
 Typical Capacity C [mAh] 1280 (discharge with high-resistance)
 Permissible Temperature Range - 20 °C ... 50 °C
 Weight, approx. [g] 11,5
 Volume [ccm] 3.8

Dimensions [mm]	min:	max:
Ø	9.5	10.5
A	-	44.5
B	43.3	-
C	4.3	-
E	-	0.5
F	-	3.8
G	0.8	-

Typical Capacities (at 20°C):



Discharge Type	Load	End Voltage[V]	0.9
1H/12H, 7D/W	50 mA	Time [h]	23,5
Digital audio		Capacity [mAh]	1177
		Energy [mWh]	1459
Discharge Type	Load	End Voltage[V]	0.9
4M/H, 8H/D, 7D/W	5,1 Ω	Time [min]	264
Portable lighting		Capacity [mAh]	1014
		Energy [mWh]	1201
Discharge Type	Load	End Voltage[V]	0.8
1H/D 7D/W	5,1 Ω	Time [min]	286
Toy		Capacity [mAh]	1028
		Energy [mWh]	1146

No publication or circulation of data to third parties without consent of VARTA Consumer Batteries

* In consideration of typical loss of capacity at storage and application.