

## YL121-0503000HV-B ADAPTÖR

FRONTPOWER



### Basic features:

- Input voltage: 100-240VAC
- Output voltage: 5-30V
- Range power:12.5Wmax
- Load Regulation: +5%
- Line Regulation: +5%
- Protections: Short-circuit/OVP/OCP
- Color:White or Black

Safety Standard	IEC 62368-1B / IEC 61558-2-16E / ETL 1310
Safety Certification	EN62368:UL/CB/CE/GS/EMC/LVD/SAA/KC/FCC/PSE/CCC EN61558:CE/GS/CB/FCC/LVD/SAA ETL 1310
Hi-pot test	Primary To Secondary: 3000VAC 10mA 1 minute or 4242VDC 10mA 3 Sec
Burn-in test	80% to 100% load, 40 C <sup>±</sup> 5°C for 4 hours
Length of DC cord	Optional
DC plug	Optional
RoHS/Reach	Yes
Package	White box or plastic bag with outer carton
AC plug	US/EU/AUS/UK/KR/JP/CCC
Surge	Over 1 KV
No Load power consumption	< 0.1w
Energy efficiency	VI
Warranty	2 years
Operating temperature	0-40 C <sup>°</sup>
Storage temperature	-20-60 C <sup>°</sup>