

# Unit UT 139C True RMS Dijital Multimetre AC DC



UNI-T'nin UT139C modeli, VFC, NCV, Max / Min / Rel ölçümlerini içeren 6000 ekran sayısına sahip True RMS otomatik dijital multimetre.

## Ana Özellikler

1. MAX / MIN / REL modları
2. Veri tutma, LED arka ışığı, otomatik kapanma
3. VFC: alçak geçiren filtre
4. Tam kapsamlı koruma (600V)
5. Gerçek RMS
6. NCV
7. Otomatik / manuel aralıkları seçilebilir

Max.Dc Akım	: 10 Amper
Max.Ac Akım	: 10 Amper
Max.Dc Volt	: 600 Dc Volt
Max.Ac Volt	: 600 Ac Volt
True RMS	: Var
Kullanım Alanı	: El Tipi Multimetre

Specifications	Range	Best Accuracy
Model	?	UT139C
DC Voltage (V)	60mV/600mV/6V/60V/600V	$\pm(0.5\%+2)$
AC Voltage (V)	60mV/600mV/6V/60V/600V	$\pm(0.8\%+3)$

DC Current (A)	600?A/6000?A/60mA/600mA/6A/10A	±(0.7%+2)
AC Current (A)	600?A/6000?A/60mA/600mA/6A/10A	±(1%+3)
Resistance (?)	600?/6k?/60k?/600k?/6M?/60M?	±(0.8%+2)
Capacitance (F)	9.999nF/99.99nF/999.9nF/9.999? F/99.99?F/999.9?F/9.999mF/99.99mF	±(4.0%+5)
Frequency (Hz)	10Hz-10MHz	±(0.1%+4)
Temperature (°C)	-40 °C~1000°C	±(1.0%+3)
Temperature (°F)	-40°F~1832°F	±(1.5%+5)
<b>Features</b>		
Display Count	?	6000
Auto Range	?	?
Manual Range	?	?
True RMS	?	?
Bandwidth (Hz)	?	45Hz ?1kHz
V.F.C	?	?
Duty Cycle	0.1% ? 99.9%	?
Diode	?	Around 3V
NCV	?	?
Auto Power Off	Around 15 minutes	?
Continuity Buzzer	?	?
Low Battery Indication	?2.5V	?
Data Hold	?	?
Relative Mode	?	?

MAX/MIN	?	?
LCD Backlight	?	?
Input Protection	600Vrms	?
Input Impedance for DCV	1G? Max	?
<b>General Characteristics</b>		
Power	AA1.5*2	
LCD Size	58mm × 36mm	
Product Colour	Red and grey	
Product Net Weight	370g	
Product Size	175mm x 81mm x 48.5mm	
Standard Accessories	Battery, test leads, temperature probe	
Standard Individual Packaging	Gift box, English manual	
Standard Quantity Per Carton	40pcs	
Standard Carton Measurement	645×450×340mm (0.098CBM per standard carton)	