

UNI-T UT 601



Specifications	Range	UT601	UT603
Resistance (Ω)	20Ω/200Ω/2kΩ/20kΩ/200kΩ/2MΩ/20MΩ/200MΩ/2000MΩ	±(0.8%+1)	
	20Ω/200Ω/2kΩ/20kΩ/200kΩ/2MΩ/20MΩ/2000MΩ		
	200Ω/2kΩ/20kΩ/200kΩ/2MΩ/20MΩ		±(0.8%+1)
Capacitance (F)	200pF/2nF/20nF/200nF/2uF/20uF/200uF/2mF/20mF	±(0.5%+10)	
	2nF/20nF/200nF/2uF/20uF/200uF/600uF		±(1%+5)
Inductance (H)	2mH/20mH/200mH/2H/20H/200H		
	2mH/20mH/200mH/2H/20H		±(2%+8)
Features			
Display count		2000	2000
Manual range		√	√
Diode		√	√
Transistor		√	√

Continuity buzzer		√	√
Low battery indication		√	√
Data hold			
General Characteristics			
Power	9V battery (6F22)		
Display	61mm x 32 mm		
Product color	Red and grey		
Product net weight	UT601/UT602: 310g, UT603: 312g		
Product size	172mm x 83mm x 38mm		
Standard accessories	Battery, test leads with alligator clips, holster		
Standard individual packing	Gift box, English manual		
Standard quantity per carton	20pcs		
Standard carton measurement	450mm x 330mm x 340mm (0.099CBM per standard carton)		
Standard carton gross weight	9.6kg		