


Rectifier Diode

Avalanche Diode

V_{RRM} = 1200-1800 V
I_{F(RMS)} = 7 A
I_{F(AV)M} = 2.3 A

| V _{RSM} V | V _{(BR)min} V | V _{RRM} V | Standard Type | Avalanche Types |
|-----------------------|---------------------------|-----------------------|------------------|--------------------|
| 1300 | 1300 | 1200 | DS 1-12D | DSA 1-12D |
| 1700 | 1750 | 1600 | | DSA 1-16D |
| 1900 | 1950 | 1800 | | DSA 1-18D |



A = Anode C = Cathode

① Only for Avalanche Diodes

| Symbol | Test Conditions | Maximum Ratings | |
|---------------------|--|-----------------|------------------|
| I _{FRMS} | T _{VJ} = T _{VJM} | 7 | A |
| I _{F(AV)M} | T _{amb} = 45°C; R _{thJA} = 38 K/W; 180° sine | 2.3 | A |
| | T _{amb} = 45°C; R _{thJA} = 80 K/W; 180° sine | 1.3 | A |
| P _{RSM} | DSA types, T _{VJ} = T _{VJM} , t _p = 10 µs | 1.6 | kW |
| I _{FSM} | T _{VJ} = 45°C; t = 10 ms (50 Hz), sine | 110 | A |
| | V _R = 0 t = 8.3 ms (60 Hz), sine | 118 | A |
| | T _{VJ} = T _{VJM} t = 10 ms (50 Hz), sine | 100 | A |
| | V _R = 0 t = 8.3 ms (60 Hz), sine | 104 | A |
| I ² t | T _{VJ} = 45°C t = 10 ms (50 Hz), sine | 60 | A ² s |
| | V _R = 0 t = 8.3 ms (60 Hz), sine | 58 | A ² s |
| | T _{VJ} = T _{VJM} t = 10 ms (50 Hz), sine | 50 | A ² s |
| | V _R = 0 t = 8.3 ms (60 Hz), sine | 45 | A ² s |
| T _{VJ} | | -40...+150 | °C |
| T _{VJM} | | 150 | °C |
| T _{stg} | | -40...+150 | °C |
| Weight | | 0.8 | g |

Features

- Plastic standard package
- Planar glassivated chips


Applications

- Low power rectifiers
- Field supply for DC motors
- Power supplies
- High voltage rectifiers

Advantages

- Space and weight savings
- Simple PCB mounting
- Improved temperature and power cycling
- Reduced protection circuits

Dimensions in mm (1 mm = 0.0394")



| Symbol | Test Conditions | Characteristic Values | | |
|-------------------|--|-----------------------|-----|------------------|
| I _R | T _{VJ} = T _{VJM} ; V _R = V _{RRM} | ≤ | 0.7 | mA |
| V _F | I _F = 7 A; T _{VJ} = 25°C | ≤ | 1.3 | V |
| V _{To} | For power-loss calculations only | 0.8 | | V |
| r _T | T _{VJ} = T _{VJM} | 67 | | mΩ |
| R _{thJA} | Forced air cooling with 1.5 m/s, T _{amb} = 45°C Soldered on to PC board, T _{amb} = 45°C | 38 | | K/W |
| d _s | Creepage distance on surface | 8.5 | | mm |
| d _A | Strike distance through air | 6.7 | | mm |
| a | Max. allowable acceleration | 100 | | m/s ² |

Data according to IEC 60747

IXYS reserves the right to change limits, test conditions and dimensions