

Aluminum Electrolytic Capacitor Specification

Series	KR1	25 V 220 μ F	Part No.	KR1-025V221ME110-T/A5.0
Customer No.	29025		Case size	Φ D6.3X L 11
Specification	Items		Standard	
	Operating temperature range		- 40 ~ + 85 $^{\circ}$ C	
	Capacitance tolerance		\pm 20% (20 $^{\circ}$ C , 120Hz)	
	Dissipation factor (MAX)		(Less than) 0.14 (20 $^{\circ}$ C , 120Hz)	
	Leakage current (MAX)		(Less than) 55 μ A (20 $^{\circ}$ C 25 V 2 min)	
	Ripple current (MAX)		275 mArms (120Hz , 85 $^{\circ}$ C)	
	Impedance (MAX)		/	
	Load life		2000 hrs	
Outline	Sleeving pipe basic		PVC	
	(Dimensions)			
	<p> The drawing shows a side view of the capacitor with a sleeve. Labels include: Vent, Sleeve, Copper clad steel wire(tinned), Markings, $\Phi 0.5 \pm 0.05$, 6.3 ± 0.5 MAX, 11 ± 1.5 max, 15min, and 4min. Polarity symbols \oplus and \ominus are shown. A top view shows the lead space as 2.5 ± 0.5. </p> <p>[Remarks: Taping space: 5.0 (+0.8-0.2)]</p> <p>(unit) : mm</p>			
Recorder	(The first edition) : 2016-5-18			
Wrote by: Luoli		Checked by: Dingchanghua		Approved by: Shenzhihong