

BW SERIES/BW系列-表面不帶電，不需絕緣套管的鐵殼熱保護器

KEY BENEFITS 產品優勢

- Case not charged, without insulating sleeve (solve installation problem of sleeve off and broken)
- Temperature sensitive
- Better pressure resistance
- 表面不帶電，不需絕緣套管 (解決安裝時套管容易脫落和破損的麻煩)
- 感溫更靈敏
- 抗壓強度更高

APPLICATION 應用範圍

- HID ballasts
- DC motor
- Battery packs
- Heating appliance
- Fractional Power Motor
- Transformer
- Ac brushless motor and pump
- 金油燈鎮流器
- 直流馬達
- 充電電池組
- 電加熱器具
- 分馬力電機
- 變壓器
- 交流無刷馬達和水泵




CERTIFICATIONS 認證

AGENCY	STANDARD NUMBER	FILE NO.	TEMP. RANGE
VDE	EN60730-2-9	40032861	30-150°C
UL	UL873	E336656	40-130°C

MAXIMUM CONTACT RATINGS

觸點最大容量

VOLTAGE	CURRENT	CYCLES
250V	6A	10000
24V	6A	10000



LEAD WIRE 導線

3398 AWG22# or Nickel strip normally length is 60mm or according to customer's require.

CODE SYSTEM 產品編號代碼圖

BW-XXX-XX°C



OPEN TEMP & RESET TEMP 額定動作溫度和復位溫度圖

產品型號	動作溫度	復位溫度	產品型號	動作溫度	復位溫度
BW-DCM-40°C	40±5°C	≥27°C	BW-DCM-95°C	95±5°C	70±15°C
BW-DCM-45°C	45±5°C	≥30°C	BW-DCM-100°C	100±5°C	70±15°C
BW-DCM-50°C	50±5°C	≥33°C	BW-DCM-105°C	105±5°C	75±15°C
BW-DCM-55°C	55±5°C	34-47°C	BW-DCM-110°C	110±5°C	75±15°C
BW-DCM-60°C	60±5°C	35-52°C	BW-DCM-115°C	115±5°C	80±15°C
BW-DCM-65°C	65±5°C	36-57°C	BW-DCM-120°C	120±5°C	85±15°C
BW-DCM-70°C	70±5°C	38-60°C	BW-DCM-125°C	125±5°C	90±15°C
BW-DCM-75°C	75±5°C	38-63°C	BW-DCM-130°C	130±5°C	95±15°C
BW-DCM-80°C	80±5°C	55±15°C	BW-DCM-135°C	135±5°C	100±15°C
BW-DCM-85°C	85±5°C	60±15°C	BW-DCM-140°C	140±5°C	105±15°C
BW-DCM-90°C	90±5°C	65±15°C	BW-DCM-145°C	145±5°C	105±15°C