


MINIATURE ALUMINUM ELECTROLYTIC CAPACITORS

SS Standard, Height 7mmL Series

- Super miniature series with 7mmL height
- Suited for use in compact audio equipment
- Load life of 2000 hours at 85°C
- Complied to the RoHS directive



Item	Characteristics									
Operating temperature range	-40 ~ +85°C									
Leakage current max.	I = 0.01CV or 4μA whichever is greater (after 1 minute)									
Capacitance tolerance	±20% at 120Hz, 20°C									
Dissipation factor max. (at 120Hz, 20°C)	WV	4	6.3	10	16	25	35, 40	50	63	
	tanδ	0.35	0.24	0.20	0.16	0.14	0.12	0.10	0.10	
Low temperature characteristics (Impedance ratio at 120Hz)	WV	4	6.3	10	16, 25	35 ~ 63				
	Z-25°C/Z+20°C	6	4	3	2	2				
	Z-40°C/Z+20°C	12	8	6	4	3				
Load life (after application of the rated voltage for 2000 hours at 85°C)	Leakage current	Less than specified value								
	Capacitance change	Within ±20% of initial value								
	tanδ	Less than 200% of specified value								
Shelf life (at 85°C)	After 1000 hours no load test, leakage current, capacitance and tanδ are same as load life value. The measurement shall be performed at 20°C by the KS C 6035 clause 5.4.									

● DRAWING (See page 99)

Unit : mm

● DIMENSIONS & MAXIMUM PERMISSIBLE RIPPLE CURRENT

μF \ WV	4	6.3	10	16	25	35	40	50	63						
1.0								4 × 7	14	4 × 7	14				
1.5								4 × 7	17	4 × 7	17				
2.2								4 × 7	21	4 × 7	21				
3.3								4 × 7	25	4 × 7	25				
4.7								4 × 7	30	4 × 7	30				
6.8						4 × 7	33	4 × 7	33	4 × 7	37	5 × 7	42		
10					4 × 7	37	4 × 7	40	4 × 7	40	5 × 7	51	5 × 7	51	
15				4 × 7	43	4 × 7	46	5 × 7	57	5 × 7	57	6.3 × 7	72	6.3 × 7	72
22			4 × 7	46	4 × 7	52	5 × 7	64	5 × 7	69	6.3 × 7	80	6.3 × 7	88	
33	4 × 7	43	4 × 7	52	4 × 7	57	5 × 7	73	5 × 7	78	6.3 × 7	98	6.3 × 7	98	
47	4 × 7	51	4 × 7	62	5 × 7	78	5 × 7	87	6.3 × 7	108					
68	5 × 7	71	5 × 7	86	5 × 7	94	6.3 × 7	122							
100	5 × 7	86	5 × 7	104	6.3 × 7	132	6.3 × 7	148							
150	6.3 × 7	122	6.3 × 7	148	6.3 × 7	162									
220	6.3 × 7	148	6.3 × 7	179											

↑ Ripple current (mA rms) at 85°C, 120Hz
 ↑ Case size ØD × L (mm)

● FREQUENCY COEFFICIENT OF PERMISSIBLE RIPPLE CURRENT

μF \ Frequency	60Hz	120Hz	1kHz	10kHz	50kHz	100kHz ≤
~ 47	0.75	1.00	1.55	2.00	2.00	2.00
68 ~ 680	0.80	1.00	1.35	1.50	1.62	1.75