


印制线路板开孔
P. C. B. HOLE DETAIL




- 1. Rating:DC12V 50mA.
- 2. Travel:0.25±0.15mm.
- 3. Contact Resistance:100mΩ Max.
- 4. Life:100,000 Cycles Min.

H (mm)	按钮顶部直径D (mm)
4.3	Ø3.5
4.5	Ø3.3
5.0	Ø3.3
5.5	Ø3.3
6.0	Ø3.3
6.5	Ø3.2
7.0	Ø3.2
7.3	Ø3.2
7.5	Ø3.2
8.0	Ø3.2
8.5	Ø3.2
9.0	Ø3.2
9.5	Ø3.2
10.0	Ø3.2
11.0	Ø3.2
11.0	Ø3.0 (客户定制)
.....

h (mm)
3.15
3.45

电路图
SCHEMATIC



序号 NO.	名称 DESCRIPTION	数量 Q'TY	材料 MATERIAL	颜色 COLOR	备注 REMARK
5	嵌件	1	黄铜	银白色	镀银
4	底座	1	PPA	黑色	——
3	弹片	1	覆银铜/不锈钢	——	镀银
2	帽头	1	PPA	——	——
1	盖板	1	黄铜	银白色	镀铜锡

NINGBO KLS ELECTRONIC CO; LTD

品名 ITEM NO.	6X6轻触开关			
料號 PART NO.	L-KLS7-TS6601-9.0-260			
圖號 DRAWING NO.	A	狀態碼		
SCALE	UNIT	mm	A4	☐

Operating Force	100±30gf	130±30gf	160±30gf	180±50gf	250±50gf	260±50gf	320±80gf	Angle	±2°	DESIGN	設計	品名	6X6轻触开关				
								6~	±0.5	CHECH	校閱	料號	L-KLS7-TS6601-9.0-260				
								3~6	±0.2			圖號	A	狀態碼			
								~3	±0.15	APPRO.	承認	SCALE	UNIT	mm	A4	☐	
工程變更通知單 ECN(DCN) NO.	版次 REV	日期 DATE	說明 DESCRIPTION				改變 CHANGE	承認 APPRO.	GENERAL TOLERANCE UNLESS OTHERWISE NOTED								