



Özellikleri

VDE 0570 / EN 61558 Normuna
Göre Vakum Dolgulu İki Bölmeli
Sarım İzolasyon Sınıfı **70° C/B**
Ağırlığı 160 Gr.

Characteristic

According to **VDE 0570 / EN 61558**
Potted under vacuum Split-Bobbini
winding Insulation Class ta **70° C/B**
Weight 160 Gr.



SİPARİŞ KODU Order No.	PRİMER [V] Primary	SEKONDER [V] Secondary	AKIM [mA] Current	PİM ARALIĞI Pim	BOŞTAKİ VOLTAJI [V] No- Load Voltage
ASL 131106	230V~	6	900	1 - 5 / 7 - 9	8,1
ASL 131108	230V~	7,5	720	1 - 5 / 7 - 9	10,1
ASL 131109	230V~	9	600	1 - 5 / 7 - 9	12,5
ASL 131112	230V~	12	450	1 - 5 / 7 - 9	16,2
ASL 131115	230V~	15	360	1 - 5 / 7 - 9	20,25
ASL 131118	230V~	18	300	1 - 5 / 7 - 9	24,3
ASL 131124	230V~	24	225	1 - 5 / 7 - 9	32,4
ASL 131206	230V~	2 x 6	2 x 450	1-5/6-7,9-10	2 x 8,1
ASL 131208	230V~	2 x 7,5	2 x 360	1-5/6-7,9-10	2 x 10,1
ASL 131209	230V~	2 x 9	2 x 300	1-5/6-7,9-10	2 x 12,1
ASL 131212	230V~	2 x 12	2 x 225	1-5/6-7,9-10	2 x 16,3
ASL 131215	230V~	2 x 15	2 x 180	1-5/6-7,9-10	2 x 20,3
ASL 131218	230V~	2 x 18	2 x 150	1-5/6-7,9-10	2 x 24,4
ASL 131224	230V~	2 x 24	2 x 112	1-5/6-7,9-10	2 x 32,6