



Özellikleri

VDE 0570 / EN 61558 Normuna Göre Vakum Dolgulu İki Bölmeli Sarım İzolasyon Sınıfı **70° C/F**
Ağırlığı 55 Gr.

Characteristic

According to **VDE 0570 / EN 61558**
Potted under vacuum Split-Bobbin winding Insulation Class ta **70° C/F**
Weight 55 Gr.



SİPARİŞ KODU Order No.	PRİMER [V] Primary	SEKONDER [V] Secondary	AKIM [mA] Current	PİM ARALIĞI Pim	BOŞTAKİ VOLTAJI [V] No-Load Voltage
ASL 108106	230V~	6	200	1 - 5 / 7 - 9	10,34
ASL 108108	230V~	7,5	160	1 - 5 / 7 - 9	13
ASL 108109	230V~	9	133	1 - 5 / 7 - 9	15,69
ASL 108112	230V~	12	100	1 - 5 / 7 - 9	20,8
ASL 108115	230V~	15	80	1 - 5 / 7 - 9	26,05
ASL 108118	230V~	18	67	1 - 5 / 7 - 9	31,9
ASL 108124	230V~	24	50	1 - 5 / 7 - 9	41,29
ASL 108206	230V~	2 x 6	2 x 100	1-5 / 6-7,9-10	2 x 10,25
ASL 108208	230V~	2 x 7,5	2 x 80	1-5 / 6-7,9-10	2 x 13
ASL 108209	230V~	2 x 9	2 x 67	1-5 / 6-7,9-10	2 x 15,6
ASL 108212	230V~	2 x 12	2 x 50	1-5 / 6-7,9-10	2 x 20,8
ASL 108215	230V~	2 x 15	2 x 40	1-5 / 6-7,9-10	2 x 26
ASL 108218	230V~	2 x 18	2 x 33	1-5 / 6-7,9-10	2 x 31,9
ASL 108224	230V~	2 x 24	2 x 25	1-5 / 6-7,9-10	2 x 41,2