



SPECIFICATION FOR APPROVAL

CUSTOMER:		DATE:		
PART NO: RC0608U-102K		DWG.NO: HX3607300		
CUSTOMER PART NO:		CUST.DWG.NO:		
(1) DIMENSION(UNIT: mm) 		A	7.5 (MAX)	m/m
		B	9.5 (MAX)	m/m
		C	15.0 ± 2.0	m/m
		D	3.0 (REF)	m/m
		E	0.6 ± 0.05	m/m
		F		m/m
		G		m/m
		H		m/m
		(2)ELECTRICAL REQUIREMENTS		(3)SCHEMATIC
L (mH)	1.0 ± 10%			
RDC (Ω)	3 (MAX)			
IDC (A)	0.35 (MAX)			
TEST CONDITION	1KHz / 0.25V			
(4)MATERIAL LIST				
NO/ITEM	MATERIAL	SUPPLIER		
CORE	DR2W 6×8(B=2.5)或同等級	SUMER		
WIRE TYPE	2UEW φ 0.16 或同等級	PACIFIC		
WINDING	180.5TS(REF)			
TUBE	UL φ 6× 10.5mm 或同等級	STARS		
		APPROVED BY 吳載敏		
		CHECKED BY 張明德		
		DRAWN BY Vivian		

CORE MASTER ENTERPRISE CO., LTD.

TEL:886-2-8919-1288 FAX:886-2-8919-1298 WEB:www.coremaster.com.tw

TEST DATA

CUSTOMER:				DATE:				
PART NO: RC0608U-102K				DWG.NO: HX3607300				
CUSTOMER PART NO :				CUST.DWG.NO :				
TEST CONDITION: 1KHz / 0.25V				DIMENSION (UNIT : mm)				
ITEM	L (mH)	RDC (Ω)	IDC (A)	A	B	C	D	E
SPEC	1.0 ± 10%	3 (MAX)	0.35 (MAX)	7.5 (MAX)	9.5 (MAX)	15.0 ± 2.0	3.0 (REF)	0.6 ± 0.05
1	0.961	2.32	OK	6.76	8.75	14.51	3.03	0.60
2	0.952	2.34	OK	6.70	8.73	14.22	3.01	0.61
3	0.966	2.32	OK	6.77	8.80	14.40	3.02	0.60
4	0.967	2.34	OK	6.73	8.79	14.38	3.02	0.60
5	0.968	2.33	OK	6.65	8.81	14.29	3.00	0.61
6	0.986	2.33	OK	6.71	8.75	14.40	3.01	0.61
7	0.974	2.31	OK	6.68	8.79	14.43	3.02	0.62
8	0.970	2.28	OK	6.69	8.82	14.40	3.02	0.61
9	0.964	2.32	OK	6.70	8.78	14.42	3.01	0.60
10	0.976	2.31	OK	6.72	8.73	14.45	3.02	0.61
\bar{X}	0.968	2.32		6.71	8.78	14.39	3.02	0.61
R	0.034	0.06		0.12	0.09	0.29	0.03	0.02
TEST INSTRUMENTS HM2791 METER FOR L 502BC						APPROVED BY 吳載敏		
						CHECKED BY 張明德		
						DRAWN BY Vivian		

CORE MASTER ENTERPRISE CO., LTD.

TEL:886-2-8919-1288 FAX:886-2-8919-1298 WEB:www.coremaster.com.tw