


# SPECIFICATION FOR APPROVAL

CUSTOMER:			DATE:		
PART NO: LCB3216-500Y-N			DWG.NO: TE9910062		
CUSTOMER PART NO:			CUST.DWG.NO:		
(1) DIMENSIONS (UNIT: mm)  			A	3.2 ± 0.2	m/m
			B	1.6 ± 0.2	m/m
			C	1.1 ± 0.2	m/m
			D	0.5 ± 0.3	m/m
			E		m/m
			F		m/m
			G		m/m
			H		m/m
			I		m/m
			J		m/m
(2) ELECTRICAL REQUIREMENTS					
Z (Ω)	50 ± 25%	TEST FREQ	100MHz / 100mV		
RDC (Ω)	0.015 (MAX)	TEST FREQ			
IDC (mA)	6000 (MAX)	TEST FREQ			
TEST INSTRUMENTS HP 4338A MILLIOHMMETER HP 4291B RF IMPEDANCE / MATERIAL ANALYZER			APPROVED BY		
			吳載敏		
			CHECKED BY		
			張明德		
			DRAWN BY		
			黃慧診		

**CORE MASTER ENTERPRISE CO., LTD.**

TEL:886-2-8919-1288    FAX:886-2-8919-1298    WEB:www.coremaster.com.tw

# TEST DATA

CUSTOMER :					DATE :				
PART NO: LCB3216-500Y-N					DWG.NO: TE9910062				
CUSTOMER PART NO :					CUST.DWG.NO :				
ITEM	Z (Ω)	RDC (Ω)	IDC (mA)		DIMENSION (UNIT : mm)				
FREQ	100MHz /100mV				A	B	C	D	
SPEC	50 ± 25%	0.015 (MAX)	6000 (MAX)		3.2 ± 0.2	1.6 ± 0.2	1.1 ± 0.2	0.5 ± 0.3	
1	44.7	0.007	OK		3.22	1.63	1.10	0.52	
2	45.8	0.007	OK		3.21	1.61	1.11	0.48	
3	44.5	0.007	OK		3.24	1.60	1.09	0.53	
4	44.8	0.006	OK		3.20	1.61	1.12	0.54	
5	44.3	0.006	OK		3.23	1.62	1.09	0.50	
6	45.0	0.006	OK		3.22	1.63	1.10	0.52	
7	42.7	0.005	OK		3.25	1.64	1.09	0.54	
8	43.6	0.007	OK		3.21	1.60	1.11	0.50	
9	45.5	0.006	OK		3.23	1.61	1.09	0.52	
10	43.8	0.006	OK		3.20	1.63	1.10	0.53	
$\bar{X}$	44.47	0.006			3.22	1.62	1.1	0.52	
R	3.1	0.002			0.05	0.04	0.03	0.06	
						APPROVED BY			
						吳載敏			
						CHECKED BY			
						張明德			
						DRAWN BY			
						黃慧診			

**CORE MASTER ENTERPRISE CO., LTD.**

TEL:886-2-8919-1288    FAX:886-2-8919-1298    WEB:www.coremaster.com.tw

# LCB3216-500Y-N

