




# SPECIFICATION FOR APPROVAL

CUSTOMER:		DATE:	
PART NO: WCB2012-201Y-N		DWG.NO: EM0644653	
CUSTOMER PART NO:		CUST.DWG.NO:	
<p>(1) DIMENSIONS (UNIT: mm)</p> <p>The drawing shows a component with a central core of wires. Dimension A is the total width, B is the width of the top section, C is the height of the top section, D is the height of the bottom section, and E is the width of the bottom section. Labels 'Epoxy' and 'Wires' indicate the materials used.</p>		A	2.0 ± 0.2 m/m
		B	1.2 ± 0.2 m/m
		C	1.2 ± 0.2 m/m
		D	0.40 (REF) m/m
		E	0.45 (REF) m/m
		F	m/m
		G	m/m
		H	m/m
		I	m/m
		J	m/m
		(2) ELECTRICAL REQUIREMENTS	
Z (Ω)	200 ± 25%	TEST FREQ	100MHz
RDC (Ω)	0.35 (MAX)	TEST FREQ	
IDC (mA)	330 (MAX)	TEST FREQ	
<p>TEST INSTRUMENTS: HP4287A RF LCR METER Chroma 16502 MILLIOHM METER</p>		<p>APPROVED BY</p>	
		<p>CHECKED BY</p>	
		<p>DRAWN BY</p>	

**CORE MASTER ENTERPRISE CO., LTD.**

TEL:886-2-8919-1288    FAX:886-2-8919-1298    WEB:www.coremaster.com.tw

# TEST DATA

CUSTOMER :				DATE :					
PART NO: WCB2012-201Y-N				DWG.NO: EM0644653					
CUSTOMER PART NO :				CUST.DWG.NO :					
ITEM	Z (Ω)	RDC (Ω)	IDC (mA)						
FREQ	100MHz								
SPEC	200 ± 25%	0.35 (MAX)	330 (MAX)						
1	213.62	0.14	OK						
2	210.98	0.14	OK						
3	218.53	0.14	OK						
4	222.80	0.14	OK						
5	209.72	0.14	OK						
6	222.13	0.14	OK						
7	213.62	0.14	OK						
8	212.46	0.14	OK						
9	213.85	0.14	OK						
10	216.38	0.14	OK						
$\bar{X}$	215.409	0.14							
R	13.08	0							
					APPROVED BY 				
					CHECKED BY 				
					DRAWN BY 				

**CORE MASTER ENTERPRISE CO., LTD.**

TEL:886-2-9819-1288    FAX:886-2-8919-1298    WEB:www.coremaster.com.tw

# WCB2012-201Y-N

