

SHIELDED SMD POWER INDUCTORS / SRI TYPE

ELECTRICAL CHARACTERISTICS FOR SRI1004

Part No.	Inductance (uH)	RDC (Ω)	IDC (A)
SRI1004-3R3 □	3.3	0.035	8.00
SRI1004-4R7 □	4.7	0.035	6.00
SRI1004-7R0 □	7.0	0.042	5.00
SRI1004-100 □	10	0.050	4.50
SRI1004-150 □	15	0.080	3.90
SRI1004-200 □	20	0.090	3.70
SRI1004-220 □	22	0.100	3.30
SRI1004-330 □	33	0.200	2.60
SRI1004-470 □	47	0.230	2.00
SRI1004-680 □	68	0.300	1.70
SRI1004-820 □	82	0.300	1.65
SRI1004-101 □	100	0.400	1.53
SRI1004-121 □	120	0.800	1.40
SRI1004-471 □	470	1.230	0.90
SRI1004-801 □	800	2.500	0.57
SRI1004-222 □	2200	5.700	0.35
SRI1004-472 □	4700	13.200	0.19

* 100uH 以上 Test Frequency : 1KHZ/1V

* 100uH 以下 Test Frequency : 100KHZ/0.1V



CORE MASTER ENTERPRISE CO., LTD.

<http://www.coremaster.com.tw>