








# SPECIFICATION FOR APPROVAL

CUSTOMER:		DATE:	
PART NO: TCV-101M-5A-10626		DWG.NO: RB6532225	
CUSTOMER PART NO:		CUST.DWG.NO:	
(1) DIMENSION(UNIT: mm)  		A	31.5 (MAX) m/m
		B	15.0 (MAX) m/m
		C	15.0 ± 2.0 m/m
		D	1.0 ± 0.1 m/m
		E	m/m
		F	m/m
		G	m/m
		H	m/m
		I	m/m
		J	m/m
		(2) ELECTRICAL REQUIREMENTS	
L (uH)	100 ± 20%		
RDC (mΩ)	36 (MAX)		
IDC (A)	5 (MAX)		
TEST CONDITION	1KHZ / 0.25V		
(4) REMAKE CORE: 盛忠 T106-26 WIRE: 2UEW φ 1.0 TURN: 32.5TS (REF) 註成品含浸。		APPROVED BY 	
		CHECKED BY 	
		DRAWN BY 	

**CORE MASTER ENTERPRISE CO., LTD.**

TEL: 886-2-8919-1288    FAX: 886-2-8919-1298    WEB: www.coremaster.com.tw

# TEST DATA

CUSTOMER:				DATE:					
PART NO: TCV-101M-5A-10626				DWG.NO: RB6532225					
CUSTOMER PART NO :				CUST.DWG.NO :					
TEST CONDITION: 1KHZ / 0.25V				DIMENSION (UNIT : mm)					
ITEM	L (uH)	RDC (mΩ)	IDC (A)	A	B	C	D		
SPEC	100 ± 20%	36 (MAX)	5 (MAX)	31.5 (MAX)	15.0 (MAX)	15.0 ± 2.0	1.0 ± 0.1		
1	99.2	29	OK	30.2	13.9	15.2	1.0		
2	99.2	29	OK	30.3	14.0	15.3	1.0		
3	99.9	29	OK	30.2	13.9	15.4	1.0		
4	99.9	29	OK	30.2	13.8	15.2	1.0		
5	98.9	29	OK	30.3	14.0	15.3	1.0		
6	100.0	29	OK	30.2	13.8	15.2	1.0		
7	100.9	29	OK	30.2	13.9	15.2	1.0		
8	99.6	29	OK	30.3	13.8	15.3	1.0		
9	99.9	29	OK	30.2	13.9	15.2	1.0		
10	99.2	29	OK	30.2	14.0	15.3	1.0		
$\bar{X}$	99.67	29		30.23	13.9	15.26	1		
R	2	0		0.1	0.2	0.2	0		
TEST INSTRUMENTS CH101 CH301A						APPROVED BY			
						CHECKED BY			
						DRAWN BY			

**CORE MASTER ENTERPRISE CO., LTD.**

TEL:886-2-8919-1288    FAX:886-2-8919-1298    WEB:www.coremaster.com.tw